

Datum: 13.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## [Nav. priklj. 330, ravno tesnjenjeN.N./N.N.Rp/Rp 2 1/2](#)

Kategorija: [Union 330, flat seat, female/female, black](#)  
Šifra: **133813RIE**

(slika je simbolična)

### Kratek opis

Fitting 330, flat sealing, IT/IT, Rp/Rp 2 1/2, black malleable iron fitting, Operating temp. -20 °C to 200 °C, ISO 7-1  
Maximum temperature and maximum operating pressure should not occur at the same time!  
According to DIN EN 10242 (previously 2950).  
Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/Rp 2 1/2
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	200