**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 25.11.2026



(slika je simbolična)

# Nav. priklj. 330, ravno tesnjenjeN.N./N.N.Rp/Rp 3/8

Kategorija: Union 330, flat seat, female/female, black
Šifra: **133806RIE**

## Kratek opis

Fitting 330, flat sealing, IT/IT, Rp/Rp 3/8, black malleable iron fitting, Operating temp. -20 °C to 200 °C, ISO 7-1
Maximum temperature and maximum operating pressure should not occur at the same time!
According to DIN EN 10242 (previously 2950).
Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj | Rp/Rp 3/8 |
| Površina | Black |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 200 |