**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 10.11.2026



(slika je simbolična)

# Nav. priklj. 331, N.N./Z.N.Rp/R 1NBR tes.,č. kovanlit. ž.

Kategorija: Union 331, flat seat, female/male, with NBR-seal
Šifra: **113174RIE**

## Kratek opis

Fitting 331, flat sealing, IT/ET, Rp/R 1, NBR seal, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galva.
"
Maximum temperature and maximum operating pressure should not occur at the same time!
Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj | Rp/R 1 |
| Površina | Hot dip galvanised |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 200 |