

Datum: 26.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[Nav. priklj. 331, N.N./Z.N.Rp/R 2 1/2,č. kovanlit. ž.](#)

Kategorija: [Union 331, flat seat, female/male, with NBR-seal](#)
Šifra: **113178RIE**

Kratek opis

Fitting 331, flat sealing, IT/ET, Rp/R 2 1/2, NBR seal,
Operating temp. -20°C to 200°C, black malleable cast iron,
Hot-dip galva.

"

Maximum temperature and maximum operating pressure
should not occur at the same time!

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for
pipe construction.

These fittings are characterized by their high mechanical
strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are
therefore suitable for drinking water

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/R 2 1/2
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	200