

Datum: 26.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Nav. priklj. 340, N.N./N.N.Rp/Rp 1/4,č. kovanlit. ž.

Kategorija: [Union 340, taper seat, female/female](#)  
Šifra: **113179RIE**

(slika je simbolična)

### Kratek opis

Fitting 340, conical sealing, IT/IT, Rp/Rp 1/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20   |
| Material                       | Black malleable iron B350-10, design symbol A |
| Navoj                          | Rp/Rp 1/4                                     |
| Površina                       | Hot dip galvanised                            |
| Standardni navoj               | acc. ISO 7-1                                  |
| Max. temperaturno območje [°C] | 300   |