

Datum: 05.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[Nav. priklj. 341, konični tesnjenje, R 3Rp 3](#)

Kategorija: [Union 341, taper seat, female/male, black](#)
Šifra: **133837RIE**

Kratek opis

Fitting 341, conical sealing, R 3, Rp 3, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.
Working minimal temperature = -20 °C, 25 bar.
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/R 3
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300