TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 15.11.2026



(slika je simbolična)

Nav. priklj. 341, N.N./Z.N.Rp/R 1,č. kovanlit. ž.

Kategorija: Union 341, taper seat, female/male
Šifra: **113193RIE**

Kratek opis

Fitting 341, conical sealing, IT/ET, Rp/R 1, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised
Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust.
These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.
Working minimal temperature = -20 °C: 25 bar.
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/R 1
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300