



(slika je simbolična)

## Okrogli cilindar, delujoč v dveh smereh, bat Ø 16, hod 100, M5

Kategorija: [Metalwork](#)  
Šifra: **105774RIE**

### Kratek opis

Round cylinder, ISO 6432, double-acting, Magnet, Piston Ø 16, Stroke 100, M5, Working pressure max. 10 bar, Temp. -10 °C to 80 °C  
Single and double-acting cylinders, with magnetic piston.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10  |
| Bat                            | Synthetic (acetal) resin                               |
| Batnica                        | C45 steel, hard chrome-plated                          |
| Cushioning                     | non-cushioned  |
| Ffunkcija                      | double-acting  |
| Gewinde Kolbenstange           | male piston rod  |
| Magnet                         | with magnet  |
| Navoj na batnici               | M6   |
| Oblika                         | Flanged joint between stainless steel barrel and heads |
| Ovoj                           | Stainless steel 1.4301                                 |
| Povezava                       | M5   |
| Standard                       | acc. to ISO 6432                                       |
| Tesnilo                        | NBR  |
| Min. nastavljeni tlak [bar]    | 0.6  |
| Max. delovni tlak [bar]        | 10   |
| Bat Ø [mm]                     | 16   |
| Max. temperaturno območje [°C] | 80   |
| Stroke [mm]                    | 100  |