



Okrogli cilinder »MI« delujoč v dveh smerehbat Ø 16hod 15M5x0.8

Kategorija: [Round cylinder, double-acting, with magnet, CA](#)
Šifra: **114818RIE**

(slika je simbolična)

Kratek opis

Round cylinder »MI« ISO 6432, double-acting, Piston Ø 16, Stroke 15, M5x0.8, Working pressure 1 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »MI« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge model
»CM« type = bottom cover with male thread, round - hinge model

Tehnične Specifikacije

| | |
|--------------------------------|------------------------|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | Stainless steel 1.4301 |
| Cushioning | non-cushioned |
| ET batnice | M6x1.0 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Ovoj | Stainless steel 1.4301 |
| Povezava | M5x0.8 |
| Serija | MI series |
| Standard | acc. to ISO 6432 |
| Tesnilo | NBR |
| Vrsta | CA type |
| Min. delovni tlak [bar] | 1 |
| Batnica Ø [mm] | 6 |
| Max. delovni tlak [bar] | 10 |
| Stroke [mm] | 15 |
| Bat Ø [mm] | 16 |
| Max. temperaturno območje [°C] | 70 |