

Datum: 04.06.2026



(slika je simbolična)

Okrogli cilindri »MSI« enosmerni, bat Ø 25, hod 80, G 1/8

Kategorija: [Round cylinder, single-acting, with magnet, CA](#)
Šifra: **114981RIE**

Kratek opis

Round cylinder »MSI«, single-acting, Magnet, Piston Ø 25, Stroke 80, G 1/8, Working pressure 2 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »M« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge model
»CM« type = bottom cover with male thread, round - hinge model

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Stainless steel 1.4301
Cushioning	non-cushioned
ET batnice	M10x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Stainless steel 1.4301
Povezava	G 1/8
Serijska	MSI series
Starting position	pressureless in the retracted position
Tesnilo	NBR
Vrsta	CA type
Min. delovni tlak [bar]	2
Batnica Ø [mm]	10
Max. delovni tlak [bar]	10
Bat Ø [mm]	25
Max. temperaturno območje [°C]	70
Stroke [mm]	80