

Datum: 19.04.2026



(slika je simbolična)

## Okrogli cilindri »MSI« enosmerni, bat Ø 40, hod 20, G 1/4

Kategorija: [Round cylinder, single-acting, with magnet, CM](#)  
Šifra: **115000RIE**

### Kratek opis

Round cylinder »MSI«, single-acting, Magnet, Piston Ø 40, Stroke 20, G 1/4, Working pressure 2 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »M« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge model  
»CM« type = bottom cover with male thread, round - hinge model

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Stainless steel 1.4301
Cushioning	non-cushioned
ET batnice	M12x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Stainless steel 1.4301
Povezava	G 1/4
Serijska	MSI series
Starting position	pressureless in the retracted position
Tesnilo	NBR
Vrsta	CM type
Min. delovni tlak [bar]	2
Max. delovni tlak [bar]	10
Batnica Ø [mm]	16
Stroke [mm]	20
Bat Ø [mm]	40
Max. temperaturno območje [°C]	70