TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 10.11.2026



(slika je simbolična)

Osn.ejektor SBP-C, izpust. vent., z dušilko, velikost šobe 2 mm

Kategorija: Basic ejector SBP-C, blow-off valve, silencer
Šifra: **108391RIE**

Kratek opis

Basic ejector »SBP-C«, Bleeder valve, Silencer, Nozzle size 2 mm, Compressed air / vacuum connection 8/10 mm, NO
Purely pneumatic vacuum generator that operates on the Venturi principle.
Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.
Properties:
• Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%)
• Connection of compressed air and vacuum with push-in coupling
• Basic housing with connection facility for a vacuum switch
• Maximum suction capacity with minimum compressed air consumption
• Minimum size, low weight
• Various power ratings for optimised air consumption
Applications:
• For universal use in handling systems with very high dynamic movements
• Handling all kinds of air-tight components
• For use in separation systems where space is restricted
• Construction of ejector blocks for centralised or decentralised individual control of suction pads

Tehnične Specifikacije

Dušilec	Plastic
Položaj sesalnega ventila v mirovanju	NO
Povezava	Push-in coupling
Sistem šobe	Brass
Telo	Plastic (impact-resistant)
Velikost šobe [mm]	2
Dovod stisnjenega zraka	8 mm
Dovod vakuuma	10 mm
Premer [mm]	20.0
Višina [mm]	72.0
Dolžina [mm]	228.0