



## Plošč.ventil HDM prik.4 mm 2x3/2NC mono ali 5/3 sredina odzračena

Kategorija: [Metalwork](#)  
Šifra: **106674RIE**

(slika je simbolična)

### Kratek opis

Valve disc for valve terminal HDM, Connection 4 mm, 2x 3/2-way, NC, monostable or 5/3-way, Centre vented. These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                  |
| IP zaščita                     | IP 65                                                |
| Material                       | aluminium                                            |
| Poskusno                       | Max. 16 (e.g. 16 spring return valves)               |
| Ročno upravljanje              | latching                                             |
| Vhodna moč                     | 0.6 W per pilot                                      |
| Ffunkcija                      | 2x 3/2-way, NC, monostable or 5/3-way, centre vented |
| Max. temperaturno območje [°C] | 60                                                   |
| Pretok [NI/min]                | 200                                                  |