TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 11.11.2026



(slika je simbolična)

Plošč.ventil HDM prik.4mm 2x3/2 NO mono ali 5/3 sredina odzračena

Kategorija: Metalwork
Šifra: **106675RIE**

Kratek opis

Valve disc for valve terminal HDM, Connect. 4 mm, 2x 3/2-way, NO, monostable or 5/3-way, Centre aerated
These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.
Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.
Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Monostable (non-latching) version of manual control also available on request.
The operating pressure is based on the installed input plates.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
IP zaščita	IP 65
Material	aluminium
Poskusno	Max. 16 (e.g. 16 spring return valves)
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot
Ffunkcija	2x 3/2-way, NO, monostable or 5/3-way, centre aerated
Max. temperaturno območje [°C]	60
Pretok [Nl/min]	200