



## Plošč.ventil HDM prik.6 mm 2x3/2 NC mono ali 5/3sredina odzračena

Kategorija: [Metalwork](#)  
Šifra: **106681RIE**

(slika je simbolična)

### Kratek opis

Valve disc for valve terminal HDM, Connection 6 mm, 2x 3/2-way, NC, monostable or 5/3-way, Centre vented. These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
IP zaščita	IP 65
Material	aluminium
Poskusno	Max. 16 (e.g. 16 spring return valves)
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot
Ffunkcija	2x 3/2-way, NC, monostable or 5/3-way, centre vented
Max. temperaturno območje [°C]	60
Pretok [NI/min]	500