



## Ploščati ventil HDM priključek 4 mm 3/2 monost. NC ali NO

Kategorija: [Metalwork](#)  
Šifra: **106676RIE**

(slika je simbolična)

### Kratek opis

Valve disc for valve terminal HDM, Connection 4 mm, 3/2-way, NC, Monostable and 3/2-way, NO, monostable. These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| IP zaščita                     | IP 65   |
| Material                       | aluminium   |
| Poskusno                       | Max. 16 (e.g. 16 spring return valves)                                    |
| Ročno upravljanje              | latching  |
| Vhodna moč                     | 0.6 W per pilot<br>3/2-way, NC,<br>monostable and 3/2-way, NO, monostable |
| Ffunkcija                      |   |
| Max. temperaturno območje [°C] | 60  |
| Pretok [NI/min]                | 200   |