

Datum: 08.01.2026



## [polietilen cevi, cevi Ø 16x12 mm, črna, rola 25 m](#)

Kategorija: [Polyethylene hose \(LD-PE\)](#)  
Šifra: **113633RIE**

(slika je simbolična)

### Kratek opis

Polyethylene hose (LD-PE), Temperature -10 °C to 60 °C,  
Hose Ø 16x12 mm, PN at 20 °C max. 9 bar, black, Roll of 25  
m

Low-priced, calibrated hose for use with screw fittings.  
With its soft and flexible character, combined with relatively  
high strengths and good resistance to stress cracking, this  
hose is ideal for use in the following types of application:

- Flexible pneumatic lines in the low-pressure range,  
providing no special resistance to greases, oils or other  
hydrocarbons is required.
- Compressed air control lines.
- Vacuum lines (suitable for vacuum up to 10 x 8 mm).
- Supply lines of all kinds.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Barva	black
Material	Polyethylene (LD- PE)
Max. obratovalni tlak pri 20 ° C [bar]	9
I.D. cevi [mm]	12
O.D. cevi [mm]	16
Dolžina koluta [m]	25
Max. temperaturno območje [°C]	60