

Datum: 24.05.2026



Polnilna enota »FUTURA« Elektr. vodena 115 V AC, Vel.1, G 3/8

Kategorija: [Filling unit, electrically operated, 115 V AC](#)
Šifra: **156627RIE**

(slika je simbolična)

Kratek opis

Filling unit »FUTURA«, electr. actuated with solenoid 115 V AC, 50 Hz, Size 1, G 3/8, Exhaust G 1/4, Input pressure 2.5 - 10 bar
The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.
The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).
It is connected and disconnected by means of the 3/2-way valve.
The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

| | |
|--|---|
| Min. temperaturno območje [°C] | -10 |
| Električni priključek | Socket coupling EN 175301-803, form C, poles 2+PE |
| IP zaščita | IP 65 |
| Izpušni zrak | G 1/4 At P ₂ = 6 bar and pressure drop Δ _p = 1 bar |
| Merjenje pretoka | G 3/8 |
| Navoj | PA66 GF60 |
| Ohišje | Material: Die-cast zinc |
| Priključni navoj | FUTURA |
| Serijska | Compressed air, neutral gases |
| Srednje | 1 |
| Velikost | 1 |
| Zaklepna moč pri 50 Hz AC napetosti [VA] | 1.6 |
| Dvižna moč pri 50 Hz AC napetosti [VA] | 2.2 |
| Min. vhodni tlak [bar] | 2.5 |
| Vhodna moč | 2.5 Watt with DC voltage |
| Max. vhodni tlak [bar] | 10 |
| D [mm] | 33.0 |
| Max. temperaturno območje [°C] | 50 |
| C [mm] | 84.8 |
| Delovni cikel [%] | 100 |
| A [mm] | 104.0 |
| B [mm] | 117.8 |
| Pretok [l/min] | 1400 |