

Datum: 21.04.2026



Polnilna enota »FUTURA«, pnevmatsko vodena, Velikost 1, G 3/8

Kategorija: [Filling units, pneumatically operated](#)
Šifra: **156633RIE**

(slika je simbolična)

Kratek opis

Filling unit »FUTURA«, pneumatically actuated, Size 1, G 3/8, Exhaust G 1/4, Input pressure 2.5 - 16 bar, Temp. -10 °C to 50 °C

The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.

The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).

It is connected and disconnected by means of the 3/2-way valve.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/4 At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Merjenje pretoka	G 3/8
Navoj	PA66 GF60
Ohišje	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	1
Velikost	2.5
Min. vhodni tlak [bar]	16
Max. vhodni tlak [bar]	33.0
D [mm]	50
Max. temperaturno območje [°C]	52.1
C [mm]	85.1
B [mm]	104.0
A [mm]	1400
Pretok [l/min]	