



Polnilna enota »FUTURA«, pnevmatsko vodena, Velikost 2, G 1/2

Kategorija: [Filling units, pneumatically operated](#)
Šifra: **156635RIE**

(slika je simbolična)

Kratek opis

Filling unit »FUTURA«, pneumatically actuated, Size 2, G 1/2, Exhaust G 1/2, Input pressure 2.5 - 16 bar, Temp. -10 °C to 50 °C

The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.

The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).

It is connected and disconnected by means of the 3/2-way valve.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Izpušni zrak | G 1/2 At P ₂ = 6 bar and pressure drop Δ _p = 1 bar |
| Merjenje pretoka | |
| Navoj | G 1/2 |
| Ohišje | PA66 GF60 |
| Priključni navoj | Material: Die-cast zinc |
| Serijska | FUTURA |
| Srednje | Compressed air, neutral gases |
| Velikost | 2 |
| Min. vhodni tlak [bar] | 2.5 |
| Max. vhodni tlak [bar] | 16 |
| Max. temperaturno območje [°C] | 50 |
| D [mm] | 56.5 |
| C [mm] | 61.1 |
| B [mm] | 117.6 |
| A [mm] | 126.0 |
| Pretok [l/min] | 3400 |