

Datum: 24.05.2026



(slika je simbolična)

Poseben filter »Stinard«PC zbir.0.01 µmVel.4,G 3/4

Kategorija: [Special filter with polycarbonate bowl](#)
Šifra: **100992RIE**

Kratek opis

Special filter »Standard« with PC container, 0.01 µm, Size 4, G 3/4, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Tehnične Specifikacije

Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Navoj	G 3/4
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container
Serijska	Standard
Rang filtra [µm]	0.01
Velikost	4
Max. vhodni tlak [bar]	16
DN	20
C [mm]	36.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
Učinkovitost [%]	99.999
A [mm]	133.0
H [mm]	134.0
D [mm]	206.0
Pretok [l/min]	7000