

Datum: 20.06.2026



(slika je simbolična)

Poseben filter »Stinard« Zašč. kletka 0.01 µm Vel.2,G 3/8

Kategorija: [Special filter with PC bowl and bowl guard](#)
Šifra: **100996RIE**

Kratek opis

Special filter »Standard« with polycarbonate container and protective cage, 0.01 µm, Size 2, G 3/8, Input pressure max. 16 bar

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At P ₂ = 6 bar and pressure drop Δ _p = 1 bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast zinc, painted silver |
| Posoda | Polycarbonate container with protective cage |
| Serija | Standard |
| Rang filtra [µm] | 0.01 |
| Velikost | 2 |
| DN | 10 |
| C [mm] | 16.0 |
| Max. vhodni tlak [bar] | 16 |
| H [mm] | 50.0 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| A [mm] | 70.0 |
| Učinkovitost [%] | 99.999 |
| D [mm] | 145.7 |
| Pretok [l/min] | 720 |