



(slika je simbolična)

## Predfilter»FUTURA«Kov. pos.0.3 µm, Vel.1, G 1/4, Pol avto.

Kategorija: [Pre-filter with metal bowl and sight glass](#)Šifra: **156562RIE**

### Kratek opis

Pre-filter »FUTURA« with metal container and viewing tube, 0.3 µm, Size 1, G 1/4, 1.5-16 bar, Temp. -10°C to 50°C, Semi-automatic  
Pre-filters in modern design for compliance with strict compressed air purity requirements.  
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.02 bar
Merjenje pretoka	G 1/4
Navoj	Semi-automatic
Odtok kondenzata	PA66 GF60
Ohišje	Metal container with viewing tube
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	0.3
Rang filtra [µm]	1
Velikost	1.5
Min. vhodni tlak [bar]	16
Max. vhodni tlak [bar]	39.5
C [mm]	50
Max. temperaturno območje [°C]	52.0
A [mm]	169.5
B [mm]	300
Pretok [l/min]	