



Predfilter»FUTURA«Kov. pos.0.3 µm, Vel.1, G 3/8, Pol avto.

Kategorija: [Pre-filter with metal bowl and sight glass](#)Šifra: **156563RIE**

(slika je simbolična)

Kratek opis

Pre-filter »FUTURA« with metal container and viewing tube, 0.3 µm, Size 1, G 3/8, 1.5-16 bar, Temp. -10°C to 50°C, Semi-automatic
Pre-filters in modern design for compliance with strict compressed air purity requirements.
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar
Merjenje pretoka	G 3/8 Semi-automatic PA66 GF60 Metal container with viewing tube
Navoj	Material: Die-cast zinc FUTURA
Odtok kondenzata	Compressed air, neutral gases
Ohišje	
Posoda	
Priključni navoj	
Serijska	
Srednje	
Rang filtra [µm]	0.3
Velikost	1
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	16
C [mm]	39.5
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	169.5
Pretok [l/min]	300