



## Predfilter »FUTURA-mali« Kov. pos. 0.3 µm, Vel. 0, G 1/4

Kategorija: [Pre-filter with metal bowl](#)  
Šifra: **142447RIE**

(slika je simbolična)

### Kratek opis

Pre-filter »FUTURA-mini« with metal container, 0.3 µm, Size 0, G 1/4, PE 1.5 - 12 bar, Temp. -10 °C to 50 °C, Fully-automatic

Pre-filters in modern design for compliance with strict compressed air purity requirements.

Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10  |
| Element filtra                 | Impregnated paper<br>At P <sub>2</sub> = 6 bar and<br>pressure drop Δ <sub>p</sub> = 0.02<br>bar |
| Merjenje pretoka               | G 1/4<br>Fully-automatic<br>PA66 GF60<br>Metal container   |
| Navoj                          | Plastic  |
| Odtok kondenzata               | FUTURA-mini  |
| Ohišje                         | Compressed air, neutral<br>gases   |
| Posoda                         | NBR  |
| Priključni navoj               | 0.3  |
| Serijski                       | 1.5  |
| Srednje                        | 12   |
| Tesnilo                        | 27.0   |
| Rang filtra [µm]               | 43.0   |
| Min. vhodni tlak [bar]         | Max. temperaturno<br>območje [°C]  |
| Max. vhodni tlak [bar]         | 50   |
| C [mm]                         | Pretok [l/min]   |
| A [mm]                         | 140  |
| Max. temperaturno območje [°C] | B [mm]   |
| Pretok [l/min]                 | 160.0  |
| B [mm]                         |  |