



(slika je simbolična)

Predfilter»FUTURA«PC zbir.0.3 µmVel.1,G 3/8Avt.

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)Šifra: **100164RIE**

Kratek opis

Pre-filter »FUTURA« with PC container and protective cage, 0.3 µm, Size 1, G 3/8, 1.5-16 bar, Temp. -10°C to 50°C, Fully-automatic
Pre-filters in modern design for compliance with strict compressed air purity requirements.
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper At $P_2 = 6$ bar and pressure drop $\Delta p = 0.02$ bar
Merjenje pretoka	G 3/8 Fully-automatic PA66 GF60 Polycarbonate container with protective cage
Navoj	Material: Die-cast zinc FUTURA
Odtok kondenzata	Compressed air, neutral gases
Ohišje	
Posoda	
Priključni navoj	
Serijska	
Srednje	
Rang filtra [µm]	0.3
Velikost	1
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	16
C [mm]	39.5
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	184.5
Pretok [l/min]	300