



(slika je simbolična)

Predfilter»FUTURA«PC zbir.0.3 µmVel.2,G 3/8Avt.

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)Šifra: **100165RIE**

Kratek opis

Pre-filter »FUTURA« with PC container and protective cage, 0.3 µm, Size 2, G 3/8, 1.5-16 bar, Temp. -10°C to 50°C, Fully-automatic
Pre-filters in modern design for compliance with strict compressed air purity requirements.
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Impregnated paper At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar |
| Merjenje pretoka | G 3/8 Fully-automatic PA66 GF60 Polycarbonate container with protective cage |
| Navoj | Material: Die-cast zinc FUTURA |
| Odtok kondenzata | Compressed air, neutral gases |
| Ohišje | |
| Posoda | |
| Priključni navoj | |
| Serijska | |
| Srednje | |
| Rang filtra [µm] | 0.3 |
| Min. vhodni tlak [bar] | 1.5 |
| Velikost | 2 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 47.8 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 63.0 |
| B [mm] | 210.8 |
| Pretok [l/min] | 500 |