



(slika je simbolična)

Predfiltrirajte brez diferencialnega tlaka, 3 µm, G 1 1/2

Kategorija: [Pre-filter without differential pressure gauge](#)
Šifra: **101558RIE**

Kratek opis

Pre-filter without differential pressure gauge, 3 µm, G 1 1/2,
Input pressure 4 - 12 bar, Medium / ambient temp. 5 °C to
60 °C

For filtering out solid impurities larger than 3 µm and for
moisture separation.

For connection upstream of a micro-filter or a combination
micro-filter/activated carbon filter.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Element filtra | Borosilicate microfibre fabric |
| Ločevanje delcev [µm] | from 3 |
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p =$ 0.5% |
| Navoj | G 1 1/2 |
| Ohišje | Aluminium |
| Posoda filtra | Aluminium |
| Rang filtra [µm] | 3 |
| Min. vhodni tlak [bar] | 4 |
| Min. sobna temperatura [°C] | 5 |
| Min. temperatura medija [°C] | 5 |
| Max. vhodni tlak [bar] | 12 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| C [mm] | 72.0 |
| Učinkovitost [%] | 99.99 |
| A [mm] | 118.0 |
| B2 [mm] | 620.0 |
| D [mm] | 858.0 |
| Pretok [l/min] | 8300 |