



(slika je simbolična)

Predfiltrirajte brez diferencialnega tlaka, 3 µm, G 1

Kategorija: [Pre-filter without differential pressure gauge](#)Šifra: **101556RIE**

Kratek opis

Pre-filter without differential pressure gauge, 3 µm, G 1,
Input pressure 4 - 12 bar, Medium / ambient temperature 5 °C to 60 °C

For filtering out solid impurities larger than 3 µm and for moisture separation.

For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Element filtra | Borosilicate microfibre fabric |
| Ločevanje delcev [µm] | from 3 |
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.5\%$ |
| Navoj | G 1 |
| Ohišje | Aluminium |
| Posoda filtra | Aluminium |
| Rang filtra [µm] | 3 |
| Min. vhodni tlak [bar] | 4 |
| Min. sobna temperatura [°C] | 5 |
| Min. temperatura medija [°C] | 5 |
| Max. vhodni tlak [bar] | 12 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| C [mm] | 72.0 |
| Učinkovitost [%] | 99.99 |
| A [mm] | 118.0 |
| B2 [mm] | 420.0 |
| D [mm] | 458.0 |
| Pretok [l/min] | 3000 |