



(slika je simbolična)

Predfiltrirajte z diferenčnim manometrom, 3 µm, G 1/2

Kategorija: [Pre-filter with differential pressure gauge](#)
Šifra: **101546RIE**

Kratek opis

Pre-filter with differential pressure gauge, 3 µm, G 1/2, Input pressure 4 - 12 bar, Medium / ambient temperature 5 °C to 60 °C

For filtering out solid impurities larger than 3 µm and for moisture separation.

For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

Tehnične Specifikacije

| | |
|---|---|
| Element filtra | Polyethylene (with 45% cavity) |
| Ločevanje delcev [µm] | from 3 |
| Merjenje pretoka | At P ₁ = 6 bar and pressure drop Δ _p = 0.5% |
| Navoj | G 1/2 |
| Ohišje | Aluminium |
| Posoda filtra | Aluminium |
| Max. označeni razpon diferenčnega manometra [bar] | 2 |
| Rang filtra [µm] | 3 |
| Min. vhodni tlak [bar] | 4 |
| Min. sobna temperatura [°C] | 5 |
| Min. temperatura medija [°C] | 5 |
| Max. vhodni tlak [bar] | 12 |
| C [mm] | 57.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 83.0 |
| Učinkovitost [%] | 99.99 |
| B2 [mm] | 335.0 |
| D [mm] | 353.0 |
| B1 [mm] | 432.5 |
| Pretok [l/min] | 1000 |