



## Prekl. ventil (3/2-smerni) »multifix«24V AC Vel.1,G 1/4

Kategorija: [On-off valves \(3/2-way valves\)](#)  
Šifra: **100617RIE**

(slika je simbolična)

### Kratek opis

Switch valve (3/2-way valve) »multifix«, 24 V AC, 50 Hz, Size 1, G 1/4, Input pressure 2 - 10 bar, Med. / ambient temp. max. 60 °C

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.  
3/2-way type including silencer.

When they are switched off, the system is relieved at the same time.

### Tehnične Specifikacije

Električni priključek	Device plug PG 9, type B, EN 175301-803
IP zaščita	IP65 (P 54) acc. to DIN 40050
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odzračevalni vtič	G 1/4
Ohišje	Die-cast zinc
Serijska	multifix
Tesnilo	NBR
Velikost	1
Min. vhodni tlak [bar]	2
Max. vhodni tlak [bar]	10
E [mm]	17.5
Solenoid	24 V AC, 50 Hz
D [mm]	26.0
C [mm]	43.7
A [mm]	47.8
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Delovni cikel [%]	100
B [mm]	138.7
Pretok [l/min]	1150