



(slika je simbolična)

Prekl. ventil (3/2-smerni) »multifix«24V DC Vel. 4G 1

Kategorija: [On-off valves \(3/2-way valves\)](#)
Šifra: **133142RIE**

Kratek opis

Switch valve (3/2-way valve) »multifix«, 24 V DC, Size 4, G 1, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is relieved at the same time.

Tehnične Specifikacije

Električni priključek	Device plug PG 9, type B, EN 175301-803
IP zaščita	IP65 (P 54) acc. to DIN 40050
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odzračevalni vtič	G 1/2
Ohišje	Die-cast aluminium
Serijska	multifix
Tesnilo	NBR
Min. vhodni tlak [bar]	2
Velikost	4
Max. vhodni tlak [bar]	16
Solenoid	24 V DC
E [mm]	35.0
C [mm]	53.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	66.0
A [mm]	85.0
Delovni cikel [%]	100
B [mm]	204.0
Pretok [l/min]	12500