

Datum: 29.06.2026



Prekl. ventil (3/2-smerni) »multifix«24V DC Vel.1,G 1/4

Kategorija: [On-off valves \(3/2-way valves\)](#)
Šifra: **100620RIE**

(slika je simbolična)

Kratek opis

Switch valve (3/2-way valve) »multifix«, 24 V DC, Size 1, G 1/4, Input pressure 2 - 10 bar, Medium / ambient temp. max. 60 °C

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.
3/2-way type including silencer.

When they are switched off, the system is relieved at the same time.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Električni priključek | Device plug PG 9, type B, EN 175301-803 |
| IP zaščita | IP65 (P 54) acc. to DIN 40050 |
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj | G 1/4 |
| Odzračevalni vtič | G 1/4 |
| Ohišje | Die-cast zinc |
| Serijska | multifix |
| Tesnilo | NBR |
| Velikost | 1 |
| Min. vhodni tlak [bar] | 2 |
| Max. vhodni tlak [bar] | 10 |
| E [mm] | 17.5 |
| Solenoid | 24 V DC |
| D [mm] | 26.0 |
| C [mm] | 43.7 |
| A [mm] | 47.8 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Delovni cikel [%] | 100 |
| B [mm] | 138.7 |
| Pretok [l/min] | 1150 |