

Datum: 02.07.2026



Prekl. ventil (3/2-smerni) »multifix-mali«110 V ACG 1/4

Kategorija: [On-off valves \(3/2-way valves\)](#)
Šifra: **100407RIE**

(slika je simbolična)

Kratek opis

Switch valve (3/2-way valve) »multifix-mini«, 110 V AC, 50 Hz, G 1/4, Input pressure 2 - 10 bar, Medium / ambient temp. max. 60 °C

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.
3/2-way type including silencer.

When they are switched off, the system is relieved at the same time.

Tehnične Specifikacije

Električni priključek	Device plug PG 9, type B, EN 175301-803
IP zaščita	IP65 (P 54) acc. to DIN 40050
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odzračevalni vtič	G 1/4
Ohišje	Die-cast zinc
Serijska	multifix-mini
Tesnilo	NBR
Min. vhodni tlak [bar]	2
Max. vhodni tlak [bar]	10
B [mm]	29.0
A [mm]	45.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	96.0
Delovni cikel [%]	100
Solenoid	110 V AC, 50 Hz
Pretok [l/min]	2000