



(slika je simbolična)

Prenosni krog. ventil za vodo, Z ročico, ročni, IT/IT, 1 1/4

Kategorija: [Potable water ball valves](#)
Šifra: **103411RIE**

Kratek opis

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20°C to 150°C, Rp 1 1/4, DN 32, PN max 30 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

| | |
|-------------------------------|----------------------------------|
| Min. delovna temperatura [°C] | -20 |
| Aplikacije | Potable water, water |
| DVGW odobritev | DIN EN 13828:2003-12, DVGW W 570 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Navoj | Rp 1 1/4 |
| Ohišje | Chrome-plated brass |
| Ročica | Steel with plastic coating |
| Standardni navoj | Thread acc. to ISO 7-1 |
| Stebelno tesnilo | NBR / FKM |
| E [mm] | 21.4 |
| PN [bar] | 30 |
| DN | 32 |
| a/f [mm] | 47 |
| B [mm] | 76.3 |
| L [mm] | 99.5 |
| A [mm] | 138.0 |
| Max. delovna temperatura [°C] | 150 |