

Datum: 01.07.2026



(slika je simbolična)

Prenosni krog. ventil za vodo, Z ročico, ročni, IT/IT, G 1, DN 25

Kategorija: [Potable water ball valves](#)
Šifra: **133165RIE**

Kratek opis

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 1, DN 25, Operating temp. -15 °C to 110 °C, PN max. 40 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -15 |
| Aplikacije | Potable water, water |
| DVGW odobritev | DIN EN 13828:2003-12, DVGW W 570 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Brass |
| Navoj | G 1 |
| Ohišje | Nickel-plated brass (outside), brass (inside) |
| Ročica | Aluminium |
| Standardni navoj | Thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo | PTFE / EPDM / HNBR |
| DN | 25 |
| PN [bar] | 40 |
| B [mm] | 57.3 |
| L [mm] | 69.0 |
| A [mm] | 105.0 |
| Max. delovna temperatura [°C] | 110 |