

Datum: 12.04.2026



(slika je simbolična)

Prenosni krogelni ventil za vodo, Z ročico, ročni, IT/IT, Rp 1/2

Kategorija: [Potable water ball valves](#)
Šifra: **103408RIE**

Kratek opis

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20°C to 150°C, Rp 1/2, DN 15, PN max. 50 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Aplikacije	Potable water, water DIN EN 13828:2003-12, DVGW W 570
DVGW odobritev	PTFE
Krogelno tesnilo	Chrome-plated brass
Krogla	Rp 1/2
Navoj	Chrome-plated brass
Ohišje	Steel with plastic coating
Ročica	Thread acc. to ISO 7-1
Standardni navoj	NBR / FKM
Stebelno tesnilo	15
DN	15.0
E [mm]	25
a/f [mm]	50
PN [bar]	50.3
B [mm]	61.0
L [mm]	92.5
A [mm]	150
Max. delovna temperatura [°C]	