

Datum: 13.04.2026



(slika je simbolična)

Prenosni krogelni ventil za vodo, Z ročico, ročni, IT/IT, Rp 2

Kategorija: [Potable water ball valves](#)
Šifra: **103413RIE**

Kratek opis

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20 °C to 150 °C, Rp 2, DN 50, PN max. 25 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Aplikacije	Potable water, water
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Navoj	Rp 2
Ohišje	Chrome-plated brass
Ročica	Steel with plastic coating
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	NBR / FKM
PN [bar]	25
E [mm]	25.7
DN	50
a/f [mm]	66
B [mm]	98.8
L [mm]	130.0
Max. delovna temperatura [°C]	150
A [mm]	158.0