

Datum: 03.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

Pretočni ventil, ET zgoraj, aluminij, krogelni ventil

Kategorija: [Check valve, male thread at top](#)
Šifra: **108425RIE**

(slika je simbolična)

Kratek opis

Flow valve, ET top, Required suction capacity $p_u = 0.3$ bar
2.3 l/min, $p_u = -0.6$ bar l/min 2,5, Aluminium, Ball seat valve
Check valves close the vacuum line if the suction pad is not
covered, thus maintaining the vacuum. The valves are
protected against dirt by a replaceable sieve. This valve
series is suitable for all suction pads in our standard range.

Tehnične Specifikacije

Navoj 1	G 1/8 ET
Navoj 2	G 1/8 IT
Ohišje	Aluminium
Vrsta gradnje	Ball seat valve (ball in brass seat)
Zahtevana stopnja evakuacije za $p_u = -0.3$ bar [l/min]	2.3
Zahtevana stopnja evakuacije za $p_u = -0.6$ bar [l/min]	2.5
Teža [g]	11.2
Dolžina [mm]	26.0
Max. Izpušna pretočna hitrost [l/min]	310