

Datum: 21.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Ravni navoj. prik. M, G 1/4 , za 4/6 mm, AF 17, PA

Kategorija: [Male connector with male G thread](#)  
Šifra: **110767RIE**

(slika je simbolična)

### Kratek opis

Straight screw-in fitting, G 1/4 o., for hose 4/6 mm, AF 17,  
Working pressure max. 10 bar (20°C)/max. 1 bar (60°C), PA  
Manufactured from high impact-resistant, UV-stabilised  
engineering plastic, extremely resistant to weathering.  
Good chemical resistance to benzine, diesel oil, fuel oil and  
alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

Narezana matica	Polypropylene (PP)
Navoj	G 1/4
Telo vijáčnega priključka	Polyamide (PA)
Vpenjalni obroč	Polypropylene (PP)
Max. delovni tlak pri 60 ° C [bar]	1
Za cevi [mm]	4/6
Max. delovni tlak pri 20 ° C [bar]	10
L2 [mm]	12.0
a/f [mm]	17
L1 [mm]	37.0