

Datum: 03.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Ravni navojni priključek M G 1/4 o., za za cev 4/6 mm, PA

Kategorija: [Male elbow with male G thread](#)  
Šifra: **110799RIE**

### Kratek opis

Angled screw-in fitting G 1/4 o., for hose 4/6 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA  
Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering.  
Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

Narezana matica	Polypropylene (PP)
Navoj	G 1/4
Telo vijáčnega priključka	Polyamide (PA)
Vpenjalni obroč	Polypropylene (PP)
Max. delovni tlak pri 60 ° C [bar]	1
Za cevi [mm]	4/6
Max. delovni tlak pri 20 ° C [bar]	10
L2 [mm]	25.0
L1 [mm]	26.0