

Datum: 12.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Ravni navojni priključek Ž G 1/8 i., za cev 6/8 mm, AF 17, PA

Kategorija: [Female connector with female G thread](#)  
Šifra: **110780RIE**

(slika je simbolična)

### Kratek opis

Straight screw-on fitting G 1/8 i., for hose 6/8 mm, AF 17, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA  
Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

Narezana matica	Polypropylene (PP)
Navoj	G 1/8
Telo vijáčnega priključka	Polyamide (PA)
Vpenjalni obroč	Polypropylene (PP)
Max. delovni tlak pri 60 ° C [bar]	1
Za cevi [mm]	6/8
Max. delovni tlak pri 20 ° C [bar]	10
a/f [mm]	17
L2 [mm]	21.0
L1 [mm]	36.0