

Datum: 02.07.2026



## Ravni pot.i fitting klik klak M5 , Cev zunanja Premer 5

Kategorija: [Male connector, parallel male thread with O-ring](#)  
Šifra: **108550RIE**

(slika je simbolična)

### Kratek opis

Straight push-in fitting »click-clock«, M5 o., for hose exterior Ø 5 mm, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.99
a/f [mm]	Ø 12
Material	Nickel-plated brass
Navoj	M5
Priporočena cev	PA, PU
Rokav	Hostaform
Serija	click-clock
Vpenjalni obroč	Stainless steel
Zunanji šesterokotnik	Without
Šestkotna glava vtičnice [mm]	2.5
Za cevi O.D. [mm]	5
Max. delovni tlak [bar]	16
L1 [mm]	22.5
Max. delovna temperatura [°C]	80