

Datum: 01.07.2026



## Ravni potisni fitting »klik klak« G 1/4 o., Cev zunanja Ø8

Kategorija: [Male connector, parallel male thread with O-ring](#)  
Šifra: **108561RIE**

(slika je simbolična)

### Kratek opis

Straight push-in fitting »click-clock«, G 1/4 o., for hose exterior Ø 8 mm, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.99
Material	Nickel-plated brass
Navoj	G 1/4
Priporočena cev	PA, PU
Rokav	Hostaform
Serija	click-clock
Vpenjalni obroč	Stainless steel
Zunanji šesterokotnik	Out
Šestkotna glava vtičnice [mm]	6
Za cevi O.D. [mm]	8
a/f [mm]	14
Max. delovni tlak [bar]	16
L1 [mm]	24.4
Max. delovna temperatura [°C]	80