



## Ravni potisni fitting »klik klak« G 1/8 o., Cev zunanja Ø 5

Kategorija: [Male connector, parallel male thread with O-ring](#)  
Šifra: **108555RIE**

(slika je simbolična)

### Kratek opis

Straight push-in fitting »click-clock«, G 1/8 o., for hose exterior Ø 5 mm, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Navoj                         | G 1/8               |
| Priporočena cev               | PA, PU              |
| Rokav                         | Hostaform           |
| Serija                        | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Zunanji šesterokotnik         | Out                 |
| Šestkotna glava vtičnice [mm] | 3                   |
| Za cevi O.D. [mm]             | 5                   |
| a/f [mm]                      | 13                  |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 22.0                |
| Max. delovna temperatura [°C] | 80                  |