

Datum: 10.07.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Ravni pregradni priključek, M18x1.5, za za cev 9/12 mm, AF 24, PA

Kategorija: [Bulkhead couplings - polyamide](#)  
Šifra: **110843RIE**

### Kratek opis

Straight bulkhead connector, M18x1.5, for hose 9/12 mm, AF 24, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

Narezana matica	Polypropylene (PP)
Navoj	M18x1.5
Telo vijáčnega priključka	Polyamide (PA)
Vpenjalni obroč	Polypropylene (PP)
Max. delovni tlak pri 60 ° C [bar]	1
Za cevi [mm]	9/12
Max. delovni tlak pri 20 ° C [bar]	10
a/f [mm]	24
L1 [mm]	84.0