

Datum: 04.04.2026



## Ravni vijačni prik. POM, G 1/8 , zun. premera 5 mm

Kategorija: [Male connector, parallel male thread with O-ring](#)  
Šifra: **110260RIE**

(slika je simbolična)

### Kratek opis

Straight screw-in fitting POM, G 1/8 o., for hose exterior Ø 5 mm, working pressure -0.95 to 16 bar  
Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.  
All our push-in fittings made of POM have the following approvals:  
drinking water DVGW, KTW, FDA and NSF.  
Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-20
Min. delovni tlak [bar]	-0.95
Material	Acetal polymer (POM)
Navoj	G 1/8
Min. delovna temperatura v vodi [°C]	1
Za cevi O.D. [mm]	5
a/f [mm]	14
Max. delovni tlak [bar]	16
L1 [mm]	22.1
Max. delovna temperatura v zraku [°C]	65
Max. delovna temperatura v vodi [°C]	70