

Datum: 13.06.2026



(slika je simbolična)

Ravni vtični konekt., rdeča. 10 mm, klik klak

Kategorija: [Reducers with push-in plug](#)Šifra: **108777RIE**

Kratek opis

Straight push-in connector, Plug nipple reducing 10 mm, »click-clock«, for hose exterior Ø 6 mm, Working pressure -0.99 to 16 bar

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Only recommended for use in combination with quick-connect fittings of the "click-clock" series.

The suitability test for use with other series is the responsibility of the user.

Tehnične Specifikacije

| | |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. delovni tlak [bar] | -0.99 |
| Material | Nickel-plated brass |
| Priporočena cev | PA, PU |
| Rokav | Hostaform |
| Serija | click-clock |
| Vpenjalni obroč | Stainless steel |
| Za cevi O.D. [mm] | 6 |
| Priključek [mm] | 10 |
| Max. delovni tlak [bar] | 16 |
| L1 [mm] | 36.2 |
| Max. delovna temperatura [°C] | 80 |