

Datum: 20.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Red. objemka 270-okroglaN.N./N.N.Rp 1/2črn

Kategorija: [Socket 270, female/female, black](#)  
Šifra: **133719RIE**

(slika je simbolična)

### Kratek opis

Bushing 270, IT/IT, Rp 1/2, black malleable iron fitting,  
Operating temp. -20 °C to 300 °C, ISO 7-1  
According to DIN EN 10242 (previously 2950).  
Malleable iron cast fittings in black steel, non-galvanized, is  
the classic fitting series in connection series in piping  
construction. Our malleable iron cast fittings are  
characterized by high mechanical strength and standardized  
fitting technology.  
Working minimal temperature = -20 °C, 25 bar.  
Working pressure for temperature range from -20 °C to 120  
°C: 25 bar.  
Working pressure for temperature range from 120 °C to 300  
°C: 20-25 bar.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp 1/2
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300