

Datum: 26.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Reducerna objemka 240, N.N./N.N.Rp 1 1/2Rp 3/4

Kategorija: [Socket 240, reducing, female/female](#)  
Šifra: **113038RIE**

(slika je simbolična)

### Kratek opis

Bushing 240, reducing, IT/IT, Rp 1 1/2, Rp 3/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	Rp 1 1/2
Navoj 2	Rp 3/4
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300